



NEW ZEALAND MADE FOR THE TRADE

SAFETY DATA SHEET

Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Silver Zinc Aerosol 400 ml
Product Code: 7544
Uses: Zinc-rich protection coating aerosol for bare metal
Company: Chemz Limited
Address: 80 Rangitane Place
Whakatu, Hastings
Telephone: +64 6 877 9690
Email: info@chemz.co.nz
Emergency Number 24 hr: 0800 764 766 (0800 POISON) National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

Classified as a dangerous goods for transport purposes.

GHS Classifications:

Aerosol Category 1
Skin irritation Category 3
Eye irritation Category 2
Reproductive toxicity Category 2
STOT (Single exposure) Category 2
STOT (single exposure) Category 3 (Narcotic)
Aquatic toxicity (chronic) Category 2
Hazardous to terrestrial vertebrates

HSNO Classifications:

2.1.2A Flammable aerosol
6.3A Irritating to the skin
6.4A Irritating to the eye
6.8B Suspected human reproductive or developmental toxicant
6.9B Harmful to human target organs or systems (Single exposure)
6.9B Harmful to human target organs (Narcotic)
9.1B Ecotoxic in the aquatic environment with long lasting effects (chronic)
9.3C Harmful to terrestrial vertebrates



Signal Words: Danger

Hazard Statements

H222 Extremely flammable aerosol.
H313 May be harmful in contact with skin.
H316 Causes mild skin irritation.
H319 May cause serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs by inhalation or if swallowed.
H412 Harmful to aquatic life with long lasting effects.
H433 Harmful to terrestrial vertebrates.



NEW ZEALAND MADE FOR THE TRADE

SAFETY DATA SHEET

Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Acetone	67-64-1	10 - 30
Xylene	1330-20-7	10 - 30
Toluene	108-88-3	10 - 30
White Spirits	8052-41-3	< 10
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	10 - 30
Non-hazardous ingredients		to 100

Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE (0800 764 766) or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.

Section 5 – FIRE-FIGHTING MEASURES

General fire hazards	Pressurised, extremely flammable aerosol.
Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. May float and be re-ignited on surface water. Will burn if involved in a fire.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
Extinguishing media:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water.
Protective equipment	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Firefighting instructions	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
Hazchem Code:	2YE

Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills:	Clean up all spills immediately. Provide ventilation. Remove all sources of ignition. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.
----------------------	---



NEW ZEALAND MADE FOR THE TRADE

SAFETY DATA SHEET

Major spills: Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

Section 7 – HANDLING AND STORAGE

Handling Precautions: Read product label before use. Keep out of reach of children.
This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use.
Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Acetone	1,185 _(bio)	2,375 _(bio)
White Spirits	525	
Toluene	188 _(skin)	-
Xylene	217	-
LPG (Liquefied petroleum gas – butane, propane)	1800	-

(bio) - Exposure can also be estimated by biological monitoring.

Additional Information: Wash hands before eating, drinking and smoking.

Engineering Controls: No controls required when handling small quantities. Use outdoors or with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation equipment and lighting should be explosion-resistant.

Protective Equipment: Generally not required for small quantities. In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

In case of inadequate ventilation wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Coloured spray, solvent odour.

pH: Not applicable.

Vapour Density: > 1 (Air =1)

Vapour Pressure, kPa: 300 - 600

Boiling Point, °C: Not applicable.

Melting Point, °C: Not applicable.

Specific Gravity: Not applicable.

Flash Point, °C: < 0 (propellant)

Explosion Limit, % v/v: LEL 1.2% UEL 9.5%

Autoignition Temp, °C: Not applicable.

Solubility: Not soluble in water.



NEW ZEALAND MADE FOR THE TRADE

SAFETY DATA SHEET

Section 10 – STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity: LD₅₀ estimated to be 2,100 mg/kg (based on component mixture, excluding propellant).

Acute Dermal Toxicity: LD₅₀ estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).

Acute Inhalation Toxicity: LC₅₀ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).

Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.

Skin Irritation: May cause skin irritation. Prolonged/repeated contact may cause defatting of the skin and dermatitis.

Eye Irritation: Spray may be irritating to the eye. Expected to be reversible in less than 7 days.

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the respiratory system.

Sensitisation: Product is not expected to be a sensitiser.

Repeated Dose Toxicity: Prolonged contact with product may result in irritant contact dermatitis.

Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity: Ecotoxic in the aquatic environment with long lasting effects.

Mobility: Product is volatile and large proportion will rapidly evaporate to the air if released into water.

Persistence/degradability: More volatile components are expected to degrade in air. Some components may be persistent and may bioaccumulate.

Section 13 – DISPOSAL CONSIDERATIONS

Material Disposal: Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.

Container Disposal: Recycle empty container if possible. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.

Section 14 – TRANSPORT INFORMATION

Transport: Classified as a Dangerous Good for transport purposes.

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.

Proper Shipping Name: Aerosols

UN Number: 1950

Dangerous Goods Class: 2.1

Subsidiary Risk: Not applicable

Packing Group: Not applicable



NEW ZEALAND MADE FOR THE TRADE

SAFETY DATA SHEET

Transport Labels Required: Class 2 Flammable (Land, Sea and Air), EHS (Sea and Air)

Land, Sea, Air Sea, Air



Marine Pollutant: Yes

EMS Number F-D, S-U (UN 1950 Flammable aerosols)

DG Segregation: This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Section 15 – REGULATORY INFORMATION

Inventory Listing NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

SDS regulations This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.

EPA Approval Number: HSR002515 Aerosols (Flammable) Group Standard 2020

EPA Hsno Controls: Refer to www.epa.govt.nz for information on Controls.
This substance is to be managed using the conditions specified in an applicable Group Standard.

Section 16 – OTHER INFORMATION

Additional information Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	AICS	Australian Inventory of Chemical Substances
	ADG	Australian Code for the Transport of Dangerous Goods by Road and Rail
	CAS	Chemical Abstract Service number
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods
	EPA	Environmental Protection Agency
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods
	LC ₅₀	Lethal Concentration, 50% / Median Lethal Concentration
	LD ₅₀	Lethal Dose, 50% / Median Lethal Dose
	LEL	Lower Explosion Limit
	mg/m ³	Milligrams per Cubic Metre
	NZIoC	New Zealand Inventory of Chemicals
	N.O.S.	Not otherwise specified
	OEL	Occupational Exposure Limit
	PEL	Permissible Exposure Limit
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)



NEW ZEALAND MADE FOR THE TRADE

SAFETY DATA SHEET

TLV	Threshold Limit Value
TWA	Time Weighted Average
UEL	Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of sds.