CHEMZ FG24
BELT GRIP

Part No. 7224 (400ml)

Eliminates belt slippage

- Suitable for incidental food contact
- A tacky formulation which adheres strongly to belts assisting transmission efficiency and drive
- The product penetrates the cord fibres to restore pliability and flexibility
- Assists in power transfer and increases belt life.
- Suitable for both indoor and outdoor belt applications irrespective of humidity or temperature
- Keeps belts flexible, pliable and resistant to cracking

CHEMZ FG24 can be used on all types of belts, flat, round or V belts
CHEMZ FG24 can be used on belts made of rubber, leather, plastic or canvas
CHEMZ FG24 non-staining and contains no resins, asphalts or mineral oil
CHEMZ FG24 increase pulling power of belt



PERFORMANCE CHARACTERISTICS	
Appearance	Clear, colourless, viscous liquid
Type of Film	Tacky, non-drying, water resistant film
Boiling Point, Initial °C	58
Temperature Range, °C	- 20 to + 170

AEROSOL PROPERTIES	
Specific Gravity	0.63
Flash Point, °C	< 0
Propellant	Hydrocarbon
Storage/Shelf Life is 5 years if stored correctly Empty aerosol container to be disposed of via metal scrap	

NSF H1 APPROVED

Nonfood Compounds Program Listed H1
Registration No.152122

MPI C26

Ministry for Primary Industries
Manatū Ahu Matua

CHEMZ FOOD GRADE