

SAFETY DATA SHEET

SDS\_ER70S6\_V1.2\_171024

---

**1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

---

**1.1 Product identifier**

Product Name: Elite Mig Wire – Solid Copper Coated Welding Wire

Part Numbers: VW80100815, VW80100915, VW80101015, VW80101215, VW80109250, VW80110250, VW80112250

**1.2 Other means of identification**

Gas metal arc welding wire

**1.3 Recommended use of the chemical and restrictions on use**

ARC Welding, Welding applications

**1.4 Details of the supplier of the product**

Supplier name: Euromarc Industries  
Address: 203 Glover Road, Hawera, NZ 4610  
Phone: 0800 278 600  
Email: [sales@euromarc.co.nz](mailto:sales@euromarc.co.nz)  
Web Site: [www.euromarc.co.nz](http://www.euromarc.co.nz)

**1.5 Emergency phone number**

Emergency Phone: 0800 POISON (0800 764 766)

---

**2. HAZARD IDENTIFICATION**

---

**2.1 Classification of the hazardous chemical**

Hazardous according to the NZ Environmental Protection Authority Criteria

**Physical Hazards**

Not classified as a Physical Hazard

**Health Hazards**

Specific Target Organ Toxicity (Repeated Exposure): Category 2

**Environmental Hazards**

Aquatic Toxicity (Acute): Category 3

**2.2 Label elements, including precautionary statements**

Signal Word: **WARNING**

Symbols:



**Hazards Statements:**

H373 may cause damage to organs through prolonged or repeated exposure.

H402 Harmful to aquatic life

**Precautionary Statements:**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

**Response Statement:**

P314 Get medical advice/attention if you feel unwell.

**Storage Statements:** None allocated.

**Disposal Statements:**

P501 dispose of contents/container in accordance with relevant regulations

**2.3 Other hazards which do not result in classification**

**General:** When this product is used in a welding process, there are a number of potential hazards. Please read and understand this Safety Data Sheet, the manufacturer's instructions. Welding arc and sparks can ignite combustibles and flammable materials.

**Electric Shock:** Electrical shock can kill.

**Radiation:** UV, IR Radiation. Arc rays can injure eyes and burn skin.

**Fumes:** Formation of dangerous fumes during use. Inhalation of welding fumes may cause respiratory irritation, cough. Excessive or prolonged inhalation of fumes may cause metal fume fever.

**Heat:** Spatter, slag, melting metal, hot welds, arc rays and sparks can cause burn injuries to skin or damage to eyes and can also ignite combustibles and flammable materials.

**Noise:** Noises generated by welding equipment may damage the auditory system.

**Magnetic fields:** Persons with a pacemaker should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device.

---

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

**3.1 Identity of chemical ingredients**

| Ingredient | CAS Number | EC Number | Content (w/w) |
|------------|------------|-----------|---------------|
| IRON       | 7439-89-6  | 231-096-4 | >96%          |
| MANGANESE  | 7439-96-5  | 231-105-1 | 0.5 to 2%     |
| SILICON    | 7440-21-3  | 231-130-8 | 0.1 to 1.15%  |
| COPPER     | 7440-50-8  | 231-159-6 | <0.35%        |
| CARBON     | 7440-44-0  | 231-153-3 | 0.06 to 0.18% |
| TITANIUM   | 7440-32-6  | 231-142-3 | <0.17%        |
| ZIRCONIUM  | 7440-67-7  | 231-176-9 | <0.15%        |
| ALUMINIUM  | 7429-90-5  | 231-072-3 | <0.15%        |

---

**4. FIRST AID MEASURES**

---

**4.1 Description of necessary first aid measures**

**Inhalation:** Remove person to fresh air, keep comfortable for breathing, and get medical advice/attention. If breathing has stopped, perform artificial respiration, and get immediate medical advice/attention.

**Skin contact:** Take off contaminated clothing, and rinse skin with soap and water [or shower]. If skin irritation occurs, get medical advice/attention. For reddened or blistered skin, or thermal burns, get medical advice/attention.

**Eye contact:** Rinse cautiously with water for several minutes. Remove contact lenses (if present and easy to do). Continue rinsing. Get medical advice/attention.

Arc rays can injure eyes. If exposed to arc rays, move victim to dark room, remove contact lenses as necessary for treatment, cover eyes with a padded dressing and rest. If symptoms persist, get medical advice/attention.

**Electric shock:** Disconnect and turn off power. If the victim is semi or unconscious, open the airway. If the victim cannot breathe, give artificial respiration. If there is no pulse, apply CPR

**Ingestion:** Unlikely due to form of product, except for granular materials. If ingested, Rinse mouth. Do NOT induce vomiting. Immediately contact the nearest poisons information centre 0800 POISON (0800 764 766)

#### **4.2 Symptoms caused by exposure**

Over exposure to metal fumes may result in metal fume fever. Symptoms resemble influenza, and usually occur several hours after exposure and include a metallic or sweet taste, chills, thirst, fever, muscle aches, chest soreness, fatigue, gastro-intestinal pain, headache, nausea and vomiting. The symptoms usually subside within one to three days of exposure with no residual effect.

Long-term (chronic) overexposure to welding fumes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects.

#### **4.3 Medical Attention and Special Treatment**

Treat symptomatically.

---

### **5. FIRE FIGHTING MEASURES**

---

#### **5.1 Extinguishing media**

Use an extinguisher agent suitable for the surrounding fire

#### **5.2 Specific hazards arising from the chemical**

Non flammable. May evolve toxic gases (metal oxides) during welding or when heated to decomposition.

#### **5.3 Advice for fire fighters**

No fire or explosion hazard exists, use standard fire fighting procedures, and consider the hazards of other involved materials

---

### **6. ACCIDENTAL RELEASE MEASURES**

---

Unlikely due to product form

Welding fumes and slags maybe released on use of this product

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

#### **6.2 Environmental precautions**

Prevent product from entering drains, sewers and waterways.

#### **6.3 Methods of cleaning up**

If spilt, collect and reuse where possible.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read and understand the manufactures instruction. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Keep formation of airborne dust and fumes to a minimum. Provide appropriate exhaust ventilation at places were dust and fumes are formed.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area, removed from incompatible substances like acids, which could cause chemical reactions. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

Exposure standards

| Ingredient                                                                                                                     | Reference | TWA |                   | STEL |                   |
|--------------------------------------------------------------------------------------------------------------------------------|-----------|-----|-------------------|------|-------------------|
|                                                                                                                                |           | ppm | mg/m <sup>3</sup> | ppm  | mg/m <sup>3</sup> |
| Aluminium metal and insoluble aluminium compounds (including pyro powder, aluminium oxide, and aluminium welding fumes), as Al | WES(NZ)   | --  | 1(r)              | --   | --                |
| Copper and its inorganic compounds, as Cu                                                                                      | WES(NZ)   | --  | 0.01(r)           | --   | --                |
| Copper, dusts & mists (as Cu)                                                                                                  | SWA(Aus)  | --  | 1                 | --   | --                |
| Iron salts, soluble, as Fe                                                                                                     | WES(NZ)   | --  | 1                 | --   | --                |
| Manganese, fume dust & compounds (as Mn)                                                                                       | WES(NZ)   | --  | 0.2               | --   | --                |
| Silicon                                                                                                                        | WES(NZ)   | --  | 10                | --   | --                |
| Zirconium & compounds, as Zr                                                                                                   | WES(NZ)   | --  | 5                 | --   | 10                |

### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well-ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust / fume levels below the recommended exposure standard.

### 8.3 Personal protective equipment (PPE)

**Eye / Face** Wear a welding helmet.

**Hands** Wear leather or welding gloves.

**Body** Wear coveralls and a leather apron / leather jacket and leather safety boots.

**Respiratory** Where an inhalation risk exists, wear a Class P2 (Metal fume) respirator. If using product in a confined area, wear an Air-line respirator.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

|                           |                      |
|---------------------------|----------------------|
| Appearance                | Wire copper coloured |
| Odour                     | Odourless            |
| Odour threshold           | Not Available        |
| Flammability              | Non flammable        |
| Flash point               | Not relevant         |
| Boiling point             | Not Available        |
| Melting point             | Not Available        |
| Evaporation rate          | Not Available        |
| pH                        | Not Available        |
| Vapour density            | Not Available        |
| Relative density          | Not Available        |
| Solubility (water)        | Insoluble            |
| Vapour Pressure           | Not Available        |
| Upper explosion limit     | Not Relevant         |
| Lower explosion limit     | Not relevant         |
| Partition coefficient     | Not Available        |
| Autoignition temperature  | Not Available        |
| Decomposition temperature | Not Available        |
| Viscosity                 | Not Available        |
| Explosive properties      | Not Available        |
| Oxidising properties      | Not Available        |

### 9.2 Other information

No additional information available

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

No additional information available

### 10.2 Chemical stability

This product is stable under normal conditions

### 10.3 Possibility of hazardous reactions

Will not occur

### 10.4 Conditions to avoid

No further information available

### 10.5 Incompatible materials

No further information available

### 10.6 Hazardous decomposition products

May evolve toxic gases (metal oxides) during welding or when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

**Acute toxicity** Acute effects of the various components of welding fumes and gases can generally be related to a particular process and exposure. Health hazards associated with welding, other than those related to fumes and gases, include electric shock, burns due to hot metal splashes, eye and skin effects of ultraviolet and infra-red radiation, effects of radiant heat, and effects of noise, for example, plasma arc welding and arc-air gouging process.

| <b>Ingredient</b> | <b>Oral LD50</b>  | <b>ATE (Oral)</b> | <b>Comments</b> |
|-------------------|-------------------|-------------------|-----------------|
| Iron              | 30000 mg/kg (rat) | --                |                 |
| Carbon            | 10000mg/kg (rat)  | --                |                 |
| Manganese         | 9000 mg/kg        | --                |                 |
| Silicon           | --                | 3160.000 mg/kg    |                 |

**Skin** Exposure to fumes evolved may cause irritation and discolouration. Contact with hot material may cause skin burns. Contact may result in an electric shock which can result in death.

**Eye** Where generated (e.g. during welding operations), arc rays may injure eyes (delayed effect) and blindness may occur. Contact with hot material may result in thermal burns.

**Sensitisation** Insufficient data for classification as a skin or respiratory sensitiser.

**Mutagenicity** Insufficient data available to classify as a mutagen.

**Carcinogenicity** Welding fume is classified as carcinogenic to humans (IARC Group 1).

**Reproductive** Insufficient data available to classify as a reproductive toxin.

**STOT – single exposure** Over exposure to metal fumes may result in metal fume fever. Symptoms resemble influenza, and usually occur several hours after exposure and include a metallic or sweet taste, chills, thirst, fever, muscle aches, chest soreness, fatigue, gastro-intestinal pain, headache, nausea and vomiting. The symptoms usually subside within one to three days of exposure with no residual effect. Harmful levels of ozone may be found in welding in confined spaces. Ozone is very irritant to the upper respiratory tract and lungs and its effects may be delayed. Symptoms include excessive mucus secretion, headache, lethargy, irritation and inflammation of the respiratory tract. In extreme cases, excess fluid and even haemorrhage may occur in the lungs. Exposure to manganese fume from welding may give rise to acute inflammation of the lungs.

**STOT – repeated exposure** Symptoms associated with repeated exposure are specific to the individual welding fume and gas components. Repeated exposure to welding fume may result in pulmonary dysfunction. Long, continued exposure to welding fume containing iron oxide may lead to the deposition of iron oxide particles in the lungs. When present in sufficient quantities the deposition is detectable on chest x-rays and can result in a benign pneumoconiosis (siderosis). Repeated exposure to manganese fume may result in manganese poisoning (manganism), a disabling, and usually progressive disorder of the central nervous system with symptoms resembling Parkinsonism.

**Aspiration** Not classified as causing aspiration

---

## 12. ECOLOGICAL INFORMATION

---

### 12.1 Toxicity

Harmful to aquatic life

### 12.2 Persistence and degradability

No information provided

### 12.3 Bio accumulative potential

No information provided

### 12.4 Mobility in soil

No information provided

### 12.5 Other adverse effects

Welding process may effect the environment if fumes are released directly into the atmosphere. Residues from welding consumables may degrade and accumulate in soils and ground water.

---

## 13. DISPOSAL CONSIDERATIONS

---

### 13.1 Waste treatment methods

**Waste disposal** Reuse where possible. No special precautions are normally required when handling this product.

**Legislation** Dispose in accordance with relevant / local legislation.

---

## 14. TRANSPORT INFORMATION

---

**NOT CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005; NZS 5433:2012, UN, IMDG OR IATA**

|                                    | LAND TRANSPORT (NZS 5433) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|------------------------------------|---------------------------|----------------------------|-----------------------------|
| <b>14.1 UN Number</b>              | None allocated            | None allocated             | None allocated              |
| <b>14.2 Proper Shipping Name</b>   | None allocated            | None allocated             | None allocated              |
| <b>14.3 Transport hazard class</b> | None allocated            | None allocated             | None allocated              |
| <b>14.4 Packing Group</b>          | None allocated            | None allocated             | None allocated              |

### 14.5 Environmental hazards

No further relevant information available

### 14.6 Special precautions for user

No further relevant information available

---

## 15. REGULATORY INFORMATION

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Approval Code** HSR002612 (2020)

**Group Standard** Metal Industry Product (Subsidiary Hazard) Group Standard 2020

**Inventory listings** NEW ZEALAND: NZIoC (New Zealand Inventory of Chemicals)

All components are listed on the NZIoC inventory, or are exempt.

---

## 16. OTHER INFORMATION

---

### Additional information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to exposures scenarios and welding techniques, processes, materials used, nature of the surface being welded and the presence of contaminants, the fumes & gases associated with welding will vary in composition and quantity. When assessing a welding process, the toxic fumes generated may not only be associated with the parent metal, filler wire or electrode. The welding/cutting arc may generate nitrogen oxides, carbon monoxide & other gases, whilst UV radiation emitted from some arcs generates ozone. Scale of use, frequency of use and current or available engineering controls must be considered.

RPE - In addition to complying with individual exposure standards for specific contaminants, where current manual welding processes are used, the fume concentration inside the welder's helmet should not exceed 5 mg/m<sup>3</sup> ( unless otherwise classified) when collected in accordance with Australian Standard AS 3853.1: Fume from welding and allied processes - Guide to methods for the sampling and analysis of particulate matter and AS 3853.2: Fume from welding and allied processes - Guide to methods for the sampling and analysis of gases. Airway irritation and metal fume fever are the most common acute effects from welding fumes.

Other gases and fumes associated with welding processes include: Inert shielding gases (e.g. argon, carbon dioxide, helium) which may reduce the atmospheric oxygen content in poorly ventilated areas. UV-radiation and Infra-Red radiation may decompose chlorinated degreasing agents to form highly toxic and irritating phosgene gas. This may occur if a metal has been degreased but inadequately dried or when vapours from a nearby degreasing bath enter the welding zone.

Welding fumes may contain a wide variety of chemical contaminants, including oxides and salts of metals and other compounds which may be generated from electrodes, filler wire, flux materials and from the welded material (e.g. painted surfaces). Welding stainless-steel and its alloys generates nickel and chromium (VI) compounds. Welding fumes are retained in the lungs. Sparingly soluble compounds may be released slowly from the lungs. Welding fume is classified as possibly carcinogenic to humans (IARC Group 2B).

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

## Abbreviations

|         |                                                                                                                                |
|---------|--------------------------------------------------------------------------------------------------------------------------------|
| ACGIH   | American Conference of Governmental Industrial Hygienists                                                                      |
| CAS #   | Chemical Abstract Service number - used to uniquely identify chemical compounds                                                |
| CCID    | Chemical Classification and Information Database (HSNO)                                                                        |
| CNS     | Central Nervous System                                                                                                         |
| EC No.  | EC No - European Community Number                                                                                              |
| EMS     | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)                                                  |
| EPA     | Environmental Protection Authority [New Zealand]                                                                               |
| GHS     | Globally Harmonized System                                                                                                     |
| HSNO    | Hazardous Substances and New Organisms                                                                                         |
| IARC    | International Agency for Research on Cancer                                                                                    |
| LC50    | Lethal Concentration, 50% / Median Lethal Concentration                                                                        |
| ATE     | Acute Toxicity Estimate (for oral and dermal exposure)                                                                         |
| OEL     | Occupational Exposure Limit pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). |
| ppm     | Parts Per Million                                                                                                              |
| RPE     | Respiratory Protective Equipment                                                                                               |
| STEL    | Short-Term Exposure Limit                                                                                                      |
| STOT-SE | Specific target organ toxicity (single exposure)                                                                               |
| STOT-RE | Specific target organ toxicity (repeated exposure)                                                                             |
| TLV     | Threshold Limit Value                                                                                                          |
| TWA     | Time Weighted Average                                                                                                          |
| WES     | Workplace exposure standards                                                                                                   |

Euromarc Industries Ltd requires that all customers read this safety data sheet carefully so as to be informed about the risks implied in the use of the product, and provide any person involved with a copy of the same and/or adequate training on the use of the product.

Whilst Euromarc Industries Ltd has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Euromarc accepts no liability for loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in the SDS.

**END OF SAFETY DATA SHEET**